

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Prüfgas 918/5

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Test gas

#### 1.3. Details of the supplier of the safety data sheet

Company name: Hekatron Vetriebs GmbH  
 Street: Brühlmatten 9  
 Place: D-79295 Sulzburg  
 Telephone: +49 7634 500-0  
 Responsible Department: E-Mail: sdb@aerosol-service.com  
 Telefax: +49 7634 6419

#### 1.4. Emergency telephone

**number:** (STIC)  
 CH-8030 Zürich National 24h-emergency telephone: 145 Switzerland: +41 44  
 251 51 51)  
 E-Mail: info@toxi.ch

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

ethyl acetate

**Signal word:** Danger

**Pictograms:**



##### Hazard statements

H222 Extremely flammable aerosol.  
 H229 Pressurised container: May burst if heated.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

##### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 2 of 10

P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Special labelling of certain mixtures

EUH018 In use may form flammable/explosive vapour-air mixture.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.  
Pressurised container: May burst if heated.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			0-5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
141-78-6	ethyl acetate			0-5 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

#### Further Information

>0.1 % according to Regulation (EC) No. 1907/2006 (REACH)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

#### After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 3 of 10

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

#### Unsuitable extinguishing media

Strong water jet

### 5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. Pressurised container: May burst if heated.

Combustible In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment (refer to section 8).

### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Do not pierce or burn, even after use. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Wear suitable protective clothing.

#### Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Provide adequate ventilation.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 4 of 10

### Hints on joint storage

Do not store together with: Pyrophoric or self-heating substances. Hazardous substances that release flammable gases when in contact with water P8 Oxidising liquids and solids Self-reactive substances and mixtures, Organic peroxides, Radioactive substances, Infectious substances

### Further information on storage conditions

Recommended storage temperature 10-30°C Do not store at temperatures above 50°C

### 7.3. Specific end use(s)

Test gas

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

### 8.2. Exposure controls



#### Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. When using do not eat, drink or smoke.

#### Eye/face protection

Wear eye protection/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 5 of 10

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol  
 Colour: clear  
 Odour: characteristic

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined  
 Initial boiling point and boiling range: -42 °C (Propan)  
 Sublimation point: not determined  
 Softening point: not determined  
 Flash point: -104 °C (Propan)

#### Flammability

Solid: not applicable  
 Gas: not applicable

#### Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: not determined  
 Upper explosion limits: not determined  
 Ignition temperature: 460-400 °C gases

#### Auto-ignition temperature

Solid: not applicable  
 Gas: not applicable

Decomposition temperature: not determined

#### Oxidizing properties

Not oxidising.

Vapour pressure: 3000-3800 hPa  
 (at 20 °C)

Vapour pressure: <12000 hPa  
 (at 50 °C)

Density: 0.5713 g/cm<sup>3</sup>

Water solubility: The study does not need to be conducted  
 because the substance is known to be  
 insoluble in water.

#### Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Flow time: not determined

Vapour density: not determined

Evaporation rate: not determined

Solvent separation test: not determined

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 6 of 10

Solvent content:

not determined

### 9.2. Other information

Solid content:

not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

In use, may form flammable/explosive vapour-air mixture. In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	5840	Rat	Safety Data Sheet OECD 401
	dermal	LD50 mg/kg	13900	Rabbit	Safety Data Sheet OECD 402
	inhalation (4 h) vapour	LC50	>25 mg/l	Rat	Safety Data Sheet OECD 403
141-78-6	ethyl acetate				
	oral	LD50 mg/kg	5620	Rabbit	Safety Data Sheet
	inhalation vapour	LC50	1600 mg/l	Rat	Safety Data Sheet

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol; ethyl acetate)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 7 of 10

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

**12.1. Toxicity**

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9.640	96 h	Pimephales promelas (fathead minnow)	Safety Data Sheet
	Acute algae toxicity	ErC50 mg/l	1.800	96 h	Green Algae	Safety Data Sheet
	Acute crustacea toxicity	EC50 mg/l	10.000	48 h	Daphnia magna (Big water flea)	Safety Data Sheet
141-78-6	ethyl acetate					
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)	Safety Data Sheet

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	<1

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.6. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Waste disposal number of used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 8 of 10

#### Waste disposal number of contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

#### Contaminated packaging

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

#### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381,959  
 Limited quantity: 1000 mL



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 9 of 10

Excepted quantity: E0  
EmS: F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Warning: Flammable gases.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40: isobutane; butane

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

##### Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Aerosol directive (75/324/EEC).

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Prüfgas 918/5

Revision date: 03.05.2019

Product code: WH21008\_WH21020

Page 10 of 10

Version 1.00, 05.12.2018, initial release

Version 1.01, 03.05.2019, Indication of changes Section 1.3

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

#### Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH018	In use may form flammable/explosive vapour-air mixture.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*